How to Change Out a Light Switch

By See Jane Drill

Copyright 2013, All Rights Reserved

Objective

The learner will be able to safely remove an existing single-pole light switch and install a new light switch, following these instructions and the accompanying video at seejanedrill.com.

Electrical Safety Precautions

The power of electricity should be respected. Electricians take basic safety precautions when working with electricity, and so should every do-it-yourselfer, to keep yourself and your family safe.

Before proceeding with the job, read and observe the following safety guidelines.

- Always shut off the power to the circuit on which you will be working. If you are unsure, shut off the power at the main breaker.
- Post a warning sign on the breaker box to let others in the house know that you are working on the electricity, and to not touch the box. Lock the box if possible. Make sure that children and pets are not present in the working area.
- Test all the wires in the open box to be sure they are dead, not just the ones you will be working on. Never assume that a box contains just one circuit. The best way to check this is with a voltage tester.
- Even after turning off the power, work as if the wires are live. Work in a methodical manner and double check the security of all connections before restoring the power.
- Wear protective shoes and clothing. Always wear rubber-soled shoes. Never work with wet feet or while standing on a wet surface. Avoid jewelry, a watch, or clothing items that might get snagged while you are working.
- Don't touch any metal while working. Make sure you grab tools by the handle (rubber-gripped tools are best). If you need to use a ladder, use a fiberglass or wooden one, NOT aluminum.

Special Note: It is dangerous and is against code to connect copper to aluminum wire.

Resources Needed to Complete Job

- Tools & Equipment
 - Needle-nose Pliers
 - Wire stripping tool
 - Phillips and flathead screwdriver
 - Multi-purpose tool or utility knife
 - Voltage indicator (Tip: To find out if your voltage indicator is working properly, try it out on a circuit that you know to be live)
 - A new single-pole light switch

Note: "Single-pole" is the most common household switch. Current versions always have one green (grounding) terminal on one side, and two brass (hot) terminals on the other side.

• Wire nuts or connectors

• General Supplies

- Electrical tape
- Flashlight (1 or 2)
- Access
 - Access to the breaker panel and the ability to turn off the power at the breaker panel. This is done by flipping the circuit breaker to the "off" position, or, completely unscrewing the fuse.

Steps to Complete Job

Part 1 - Remove Existing Light Switch

1. The very first step is to take the appropriate safety precautions. If you have not already done so, review and observe the safety precautions listed in detail on page 1.

- 2. Disconnect and remove the existing switch:
 - a. Remove the top and bottom screws that are bolting the switch to the wall.
 - b. Gently pull the switch slightly out of the box, so that the terminals and wires are exposed, being careful to not disturb the wires too much.
 - c. Disconnect the ground, which is a bare copper or green-sheathed wire attached to a green terminal. You will do this by loosening the terminal or grounding screw, and lifting out the wire.



Existing Ground Wire

- d. On the other side of the switch, you will find the two hot or black wires, attached to brass terminals. Disconnect those as well.
- e. Remove switch.

Part 2 - Install New Switch

1. Ensure that the 3 wires are prepared for the new switch. There should be enough bare exposed wire to fit around the terminals of the new switch, and they should be formed into loops that look somewhat like a question mark. You may need to strip them with your wire strippers and/or re-form them with your needle-nose pliers. If you have any questions about how to do this, please refer to the See Jane Drill video "How to Strip Wire and Wire a Single-Pole Switch".



Properly Formed Hot Wire

3. Attach the ground wire: Loop the copper (or green-sheathed) wire around the green terminal. Tighten with a screwdriver.

Handy Tip from Leah: Whenever you are attaching wire to a terminal, you want to be sure that it is looping "on" to the terminal. What this means is that when you tighten the terminal screw, the wire will tighten in to the screw, not away from the screw. See picture following step 4 for what this looks like.

4. Attach the hot wires: Attach the black wires to the brass terminals, again, being careful to ensure that you are not backing the wires out when you tighten the screws. What this usually means when you are coming from this side of the switch is that you need to loop the black wires from the bottom. See picture below.



Correctly Attached Hot Wires

- 5. Place switch back in the wall and secure it to the box by tightening the top and bottom screws. Do not tighten them all the way, as you may need to adjust the switch position to accommodate the cover plate.
- 6. Attach the cover plate. If you need to adjust the switch position to fit inside the cover plate, remove the cover plate, slide the switch slightly to the left or right as needed. Then, tighten the screws on the top and bottom of the switch. Attach the cover plate.
- 7. Turn the power back on at the breaker, and test the switch. The light should come on.

And that is it. You did it! You have just replaced a light switch.

For further information about the task described in this worksheet and the tools and materials needed to complete this job, refer to **www.seejanedrill.com**

Note: It is the intention of See Jane Drill to educate and empower people to perform their own home repairs. However, if, after viewing the video and reading the safety precautions and instructions, you still feel uncomfortable with performing an electrical job, you may want to call an electrician. Safety is the number one priority.

Due to differing conditions, tools, and individual skills, See Jane Drill assumes no responsibility for any mistakes, damages, injuries suffered, or losses incurred as a result of following the information published on our website and in the videos and written instructions published through our website. Before beginning any project, review the instructions carefully, and if you still have any doubts or questions about how to complete the project, consult with local experts or authorities. Also, because codes and regulations vary greatly by location, you should check to

ensure that your project complies with all applicable local codes and regulations. Always read and follow all the safety precautions provided by any tool or equipment manufacturer, and follow all accepted safety procedures.

See Jane Drill is dedicated to providing accurate and helpful do-it-yourself information. We welcome your questions, input and feedback about the information provided on this website.